

FEATURES

- Revolutionary positive securing system prevents unintentional power disconnection
- Patented C14 positive mechanism locks with P-Lock outlets and is backward compatible with any standard C13 outlet
- Fit for high density multi-outlets design
- Multi-angle plug option subject to special order
- Rated up to 15 Amps
- Various colors /length available
- Stock available in Czechia as off early August 2022



TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz)
Rating	UL/cUL : 10A/13A/15A 250VAC TUV or VDE : 10A 250VAC
Operation temperature	-20° C ~ +70° C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better Cable: UL VW-1, IEC60332-1. Cat F2
Conductor Size Option	Europe : 0.75mm ² / 1.0 mm ²

COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation Industrial
- Industrial Equipment
- Architectural devices
- Broadcasting stations
- Critical Power Management

APPROVALS



SPECIFICATION

61413X - XX XYZ X

Plug Angle Option

0=Straight 1=Right 2=Left
3=Up 4=Down

Color Options: (Actual color may vary)

0=Black 1=Gray 2=Blue
3=Purple 4=Green 6=Orange
7=Red 8=Yellow 9=White

WIRE TYPE:
Europe: 13=0.75mm²/H05VV-F, 23=1.0mm²/H05VV-F

CABLE LENGTH:
Europe: X=meter, YZ=cm